

Drain body The Universal DN 100, 3 inlets, w. backwater valve



Article information

Item no.: 27600
GTIN: 4026092085141
Price group: 10

Advantages

- Flexible installation: vertically adjustable upper section rotatable
- Integrated backwater protection
- vertically adjustable

Description

The polymer drain body is equipped with a removable backwater valve with two backwater flaps, one hand-lockable emergency closure and a sludge bucket. The drain body also has two inlets DN 50 and one inlet DN 70 with blind plug. Material:

PP

Variant

Waterproof flange:

Waterproofing layer on the drain body:

Sealing water height:

Mechanical backwater flaps:

Pre-assembled at the factory

Connection flange

60 mm

2

General characteristics

Colour:

Standard:

Nominal size (DN):

Outer diameter (OD):

Type of wastewater:

Installation situation:

Delivery state:

Backwater protection:

black

EN 1253

100

110 mm

without sewage

floor slab installation

installation-ready

Type 5

Dimensions

Net weight:

Gross weight:

Vertical adjustment:

Length:

Width:

Height:

2,31 kg

2,31 kg

vertically adjustable upper section

380 mm

285 mm

190 mm

Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Material of drain body:	PP
System:	lateral
Coverage features	
Odour trap:	included