

Yard drain System 100, vert., slot grat., B 125



Article information

Item no.: 67110B
GTIN: 4026092039373
Price group: 10

Advantages

- Recyclable
- Fulfills highest sound protection requirements
- Temperature-resistant up to 400 degrees Celsius

Description

The Ecoguss yard drain is used for point drainage and is equipped with a sludge bucket. The recyclable composite material, Ecoguss fulfils the highest sound protection requirements, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. The outlet socket is suitable for connection to polymer pipes. Separate equipotential bonding is not necessary.

Variant	
System:	100
Contents of sludge trap:	yes
General characteristics	
Nominal size (DN):	100
Dimensions	
Net weight:	2,9 kg
Gross weight:	2,9 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Number of outlets:	1
Material of drain body:	Polymer
System:	vertical
Coverage features	
Type of cover:	Round slotted cover
Cover material:	Ecoguss
Colour of cover:	black
Width of cover:	247 mm

Length of cover:	247 mm
Surface:	EDM
Cover locking:	Lock & Lift
Load class:	B 125 (EN 124)
Shape of upper section:	square
Upper section material:	Ecoguss
Contents of sludge trap:	yes
Odour trap:	no