

Backwater valve Staufix Basic OD 100, Type 0, w/o emergency closure



Article information

Item no.: 76100
GTIN: 4026092011300
Price group: 10

Advantages

- Simple conversion possible using conversion kits
- Fast and toolless maintenance and cleaning
- Ideal for modernisation, can also be installed in existing pipes later

Description

The backwater valve for rainwater is equipped with a mechanical flap which closes automatically in the event of backwater. Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second backwater flap or an emergency closure.

Variant

Mechanical backwater flaps: 1

General characteristics

| | |
|-------------------------|-----------------------|
| Colour: | black |
| Standard: | EN 13564 |
| Nominal size (DN): | 100 |
| Outer diameter (OD): | 100 mm |
| Type of wastewater: | Rainwater |
| Installation situation: | exposed drainage pipe |
| Delivery state: | installation-ready |
| Backwater protection: | Type 0 |

Dimensions

| | |
|---|--------|
| Net weight: | 1,2 kg |
| Gross weight: | 1,2 kg |
| Vertical drop between inlet and outlet: | 9 mm |
| Length: | 355 mm |
| Width: | 155 mm |
| Height: | 170 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

Coverage features

Adjustment range:

screwed